GNUPLOT

An Interactive Plotting Program

Thomas Williams & Colin Kelley

Version 3.0 organized by: Gershon Elber
Version 3.0 major contributors (alphabetic order):
John Campbell
Gershon Elber
David Kotz
Ed Kubaitis
Russell Lang
Tom Tkacik
Alex Woo

Mailing list for comments: `info-gnuplot@ames.arc.nasa.gov`
Mailing list for bug reports: `bug-gnuplot@ames.arc.nasa.gov`

This manual is for GNUPLOT version 3.2

Contents

1 Gnuplot **1**

2 Cd **1**

3 Clear **1**

4 Command-line editing **1**

5 Comment **2**

6 Environment **2**

7 Exit **3**

8 Expressions **3**

8.1 Functions . . . 3

8.2 Operators . . . 4

8.2.1 Binary . . . 4

8.2.2 Unary . . . 5

9 Help **5**

10 Load **6**

11 Pause **6**

12 Plot **6**

12.1 Data-file . . . 7

12.1.1 Using . . . 8

12.2 Errorbars . . . 10

12.3 Parametric . . . 10

12.4 Ranges . . . 11

12.5 Style . . . 12

12.6 Title . . . 13

13 Print **13**

14 Pwd **13**

15 Quit **14**

16 Replot **14**

17 Save **14**

18 Set-show **14**

18.1 Angles . . . 14
18.2 Arrow . . . 15
18.3 Autoscale . . . 15
18.3.1 Parametric mode . . . 16
18.4 Border . . . 17
18.5 Clip . . . 17
18.6 Cntrparam . . . 17
18.7 Contour . . . 18
18.8 Data style . . . 18
18.9 Dummy . . . 18
18.10 Format . . . 19
18.11 Function style . . . 19
18.12 Functions . . . 19
18.13 Grid . . . 20
18.14 Hidden3d . . . 20
18.15 Isosamples . . . 20
18.16 Key . . . 20
18.17 Label . . . 21
18.18 Logscale . . . 22
18.19 Mapping . . . 22
18.20 Offsets . . . 23
18.21 Output . . . 23
18.22 Parametric . . . 23
18.23 Polar . . . 24
18.24 Rrange . . . 25
18.25 Samples . . . 25
18.26 Size . . . 25
18.27 Style . . . 26
18.28 Surface . . . 26
18.29 Terminal . . . 27
18.29.1 Dumb . . . 27
18.29.2 Hpljii . . . 27
18.29.3 Iris4d . . . 27
18.29.4 Pbm . . . 28
18.29.5 Postscript . . . 28
18.29.6 Aifm . . . 29
18.29.7 Table . . . 29
18.30 Tics . . . 29
18.31 Time . . . 30

18.32 Title 30
18.33 Trange 31
18.34 Urange 31
18.35 Variables 31
18.36 View 31
18.37 Vrange 32
18.38 Xlabel 32
18.39 Xrange 32
18.40 Xtics 33
18.41 Xzeroaxis 33
18.42 Ylabel 33
18.43 Yrange 34
18.44 Ytics 34
18.45 Yzeroaxis 34
18.46 Zero 35
18.47 Zeroaxis 35
18.48 Zlabel 35
18.49 Zrange 35
18.50 Ztics 36

19 Shell **36**

20 Splot **36**

21 Start-up **36**

22 Substitution **36**

23 User-defined **37**

24 Bugs **37**

1 Gnuplot

GNUPLOT is a command-driven interactive function plotting program. It is case sensitive (commands and function names written in lowercase are not the same as those written in CAPS). All command names may be abbreviated, as long as the abbreviation is not ambiguous. Any number of commands may appear on a line, separated by semicolons (;). Strings are indicated with quotes. They may be either single or double quotation marks, e.g.,

```
load "filename"
cd 'dir'
```

Any command-line arguments are assumed to be names of files containing GNUPLOT commands, with the exception of standard X11 arguments, which are processed first. Each file is loaded with the **load** command, in the order specified. GNUPLOT exits after the last file is processed. When no load files are named, gnuplot enters into an interactive mode.

Commands may extend over several input lines, by ending each line but the last with a backslash (\). The backslash must be the LAST character on each line. The effect is as if the backslash and newline were not there. That is, no white space is implied, nor is a comment terminated. Therefore, commenting out a continued line comments out the entire command (see **comment**).

In this documentation, curly braces ({}) denote optional arguments to many commands, and a vertical bar (|) separates mutually exclusive choices. GNUPLOT keywords or help topics are indicated by backquotes or **boldface** (where available). Angle brackets (<>) are used to mark replaceable tokens.

For help on any topic, type **help** followed by the name of the topic.

The new GNUPLOT user should begin by reading about the **plot** command (type **help plot**).

2 Cd

The **cd** command changes the working directory.

Syntax:

```
cd "<directory-name>"
```

The directory name must be enclosed in quotes.

Examples:

```
cd 'subdir'
cd ".."
```

3 Clear

The **clear** command erases the current screen or output device as specified by **set output**. This usually generates a formfeed on hardcopy devices. Use **set terminal** to set the device type.

4 Command-line editing

The Unix and IBM PC versions of GNUPLOT support command-line editing. Also, a history mechanism allows previous commands to be edited, and re-executed. After the command line has been edited, a newline or carriage return will enter the entire line regardless of where the cursor is positioned.

The editing commands are as follows:

Character	Function
	Line Editing
^B	move back a single character.
^F	move forward a single character.
^A	move to the beginning of the line.
^E	move to the end of the line.
^H, DEL	delete the previous character.
^D	delete the current character.
^K	delete from current position to the end of line.
^L, ^R	redraw line in case it gets trashed.
^U	delete the entire line.
^W	delete from the current word to the end of line.
	History
^P	move back through history.
^N	move forward through history.

On the IBM PC the use of a TSR program such as DOSEDIT or CED may be desired for line editing. For such a case GNUPLOT may be compiled with no line editing capability (default makefile setup). Set READLINE in the makefile and add readline.obj to the link file if GNUPLOT line editing is to be used for the IBM PC. The following arrow keys may be used on the IBM PC version if readline is used:

Arrow key	Function
Left	same as ^B.
Right	same as ^F.
Ctl Left	same as ^A.
Ctl Right	same as ^E.
Up	same as ^P.
Down	same as ^N.

(The readline function in gnuplot is not the same as the readline used in GNU BASH and GNU EMACS. It is somewhat compatible however.)

5 Comment

Comments are supported as follows: a # may appear in most places in a line and GNUPLOT will ignore the rest of the line. It will not have this effect inside quotes, inside numbers (including complex numbers), inside command substitutions, etc. In short, it works anywhere it makes sense to work.

6 Environment

A number of shell environment variables are understood by GNUPLOT. None of these are required, but may be useful.

If GNUTERM is defined, it is used as the name of the terminal type to be used. This overrides any terminal type sensed by GNUPLOT on start up, but is itself overridden by the .gnuplot (or equivalent) start-up file (see **start-up**), and of course by later explicit changes.

On Unix, AmigaDOS, and MS-DOS, GNUHELP may be defined to be the pathname of the HELP file (gnuplot.gih).

On VMS, the symbol GNUPLOT$HELP should be defined as the name of the help library for GNUPLOT.

On Unix, HOME is used as the name of a directory to search for a .gnuplot file if none is found in the current directory. On AmigaDOS and MS-DOS, GNUPLOT is used. On VMS, SYS$LOGIN: is used. See help start-up.

On Unix, PAGER is used as an output filter for help messages.

On Unix and AmigaDOS, SHELL is used for the **shell** command. On MS-DOS, COMSPEC is used for the **shell** command.

On AmigaDOS, GNUFONT is used for the screen font. For example: "setenv GNUFONT sapphire/14".

On MS-DOS, if the BGI interface is used, the variable **BGI** is used to point to the full path to the BGI drivers directory. Furthermore SVGA is used to name the Super VGA BGI driver in 800x600 res., and its mode of operation as 'Name.Mode'. For example, if the Super VGA driver is C:\TC\BGI\SVGADRV.BGI and mode 3 is used for 800x600 res., then: 'set BGI=C:\TC\BGI' and 'set SVGA=SVGADRV.3'.

7 Exit

The commands **exit** and **quit** and the END-OF-FILE character will exit GNUPLOT. All these commands will clear the output device (as the **clear** command does) before exiting.

8 Expressions

In general, any mathematical expression accepted by C, FORTRAN, Pascal, or BASIC is valid. The precedence of these operators is determined by the specifications of the C programming language. White space (spaces and tabs) is ignored inside expressions.

Complex constants may be expressed as the {<real>,<imag>}, where <real> and <imag> must be numerical constants. For example, {3,2} represents 3 + 2i; {0,1} represents **i** itself. The curly braces are explicitly required here.

8.1 Functions

The functions in GNUPLOT are the same as the corresponding functions in the Unix math library, except that all functions accept integer, real, and complex arguments, unless otherwise noted. The **sgn** function is also supported, as in BASIC.

Function	Arguments	Returns
abs(x)	any	absolute value of `x`, $\|x\|$; same type
abs(x)	complex	length of `x`, $\sqrt{\text{real}(x)^2 + \text{imag}(x)^2}$
acos(x)	any	$\cos^{-1} x$ (inverse cosine) in radians
arg(x)	complex	the phase of x in radians
asin(x)	any	$\sin^{-1} x$ (inverse sin) in radians
atan(x)	any	$\tan^{-1} x$ (inverse tangent) in radians
besj0(x)	radians	j_0 Bessel function of x
besj1(x)	radians	j_1 Bessel function of x
besy0(x)	radians	y_0 Bessel function of x
besy1(x)	radians	y_1 Bessel function of x
ceil(x)	any	$\lceil x \rceil$, smallest integer not less than x (real part)
cos(x)	radians	$\cos x$, cosine of x
cosh(x)	radians	$\cosh x$, hyperbolic cosine of x
exp(x)	any	e^x, exponential function of x
floor(x)	any	$\lfloor x \rfloor$, largest integer not greater than x (real part)
gamma(x)	any	$\Gamma(\text{real}(x))$, gamma function of real(x)
imag(x)	complex	imaginary part of x as a real number
int(x)	real	integer part of x, truncated toward zero
log(x)	any	$\log_e x$, natural logarithm (base e) of x
log10(x)	any	$\log_{10} x$, logarithm (base 10) of x
real(x)	any	real part of x
sgn(x)	any	1 if $x > 0$, -1 if $x < 0$, 0 if $x = 0$. imag(x) ignored
sin(x)	radians	$\sin x$, sine of x
sinh(x)	radians	$\sinh x$, hyperbolic sine x
sqrt(x)	any	$\sqrt{x}$, square root of x
tan(x)	radians	$\tan x$, tangent of x
tanh(x)	radians	$\tanh x$, hyperbolic tangent of x

8.2 Operators

The operators in GNUPLOT are the same as the corresponding operators in the C programming language, except that all operators accept integer, real, and complex arguments, unless otherwise noted. The ** operator (exponentiation) is supported, as in FORTRAN.

Parentheses may be used to change order of evaluation.

8.2.1 Binary

The following is a list of all the binary operators and their usages:

Binary Operators		
Symbol	Example	Explanation
`**`	`a**b`	exponentiation
`*`	`a*b`	multiplication
`/`	`a/b`	division
`%`	`a%b`	* modulo
`+`	`a+b`	addition
`-`	`a-b`	subtraction
`==`	`a==b`	equality
`!=`	`a!=b`	inequality
`&`	`a&b`	* bitwise AND
`^`	`a^b`	* bitwise exclusive OR
`|`	`a|b`	* bitwise inclusive OR
`&&`	`a&&b`	* logical AND
`||`	`a||b`	* logical OR
`?:`	`a?b:c`	* ternary operation

(*) Starred explanations indicate that the operator requires integer arguments.

Logical AND (&&) and OR (||) short-circuit the way they do in C. That is, the second && operand is not evaluated if the first is false; the second || operand is not evaluated if the first is true.

The ternary operator evaluates its first argument (a). If it is true (non-zero) the second argument (b) is evaluated and returned, otherwise the third argument (c) is evaluated and returned.

8.2.2 Unary

The following is a list of all the unary operators and their usages:

Unary Operators		
Symbol	Example	Explanation
`-`	`-a`	unary minus
`~`	`~a`	* one's complement
`!`	`!a`	* logical negation
`!`	`a!`	* factorial

(*) Starred explanations indicate that the operator requires an integer argument.

The factorial operator returns a real number to allow a greater range.

9 Help

The **help** command displays on-line help. To specify information on a particular topic use the syntax:

```
help {<topic>}
```

If <topic> is not specified, a short message is printed about GNUPLOT. After help for the requested topic is given, help for a subtopic may be requested by typing its name, extending the help request. After that subtopic has been printed, the request may be extended again, or simply pressing return goes back one level to the previous topic. Eventually, the GNUPLOT command line will return.

10 Load

The **load** command executes each line of the specified input file as if it had been typed in interactively. Files created by the **save** command can later be **load**ed. Any text file containing valid commands can be created and then executed by the **load** command. Files being **load**ed may themselves contain **load** commands. See **comment** for information about comments in commands.

The **load** command must be the last command on the line.

Syntax:

```
load "<input-file>"
```

The name of the input file must be enclosed in quotes.

Examples:

```
load 'work.gnu'
load "func.dat"
```

The **load** command is performed implicitly on any file names given as arguments to GNUPLOT. These are loaded in the order specified, and then GNUPLOT exits.

11 Pause

The **pause** command displays any text associated with the command and then waits a specified amount of time or until the carriage return is pressed. **pause** is especially useful in conjunction with **load** files.

Syntax:

```
pause <time> {"<string>"}
```

<time> may be any integer constant or expression. Choosing -1 will wait until a carriage return is hit, zero (0) won't pause at all, and a positive integer will wait the specified number of seconds.

Note: Since **pause** is not part of the plot it may interact with different device drivers differently (depending upon how text and graphics are mixed).

Examples:

```
pause -1    # Wait until a carriage return is hit
pause 3     # Wait three seconds
pause -1  "Hit return to continue"
pause 10  "Isn't this pretty?  It's a cubic-spline."
```

12 Plot

plot and **splot** are the primary commands of the program. They plot functions and data in many, many ways. **plot** is used to plot 2-d functions and data, while **splot** plots 3-d surfaces and data.

Syntax:

```
plot {ranges}  <function> {title} {style}
            {, <function> {title} {style}...}
```

```
splot {ranges}  <function> {title} {style}
             {, <function> {title} {style}...}
```

where <function> is either a mathematical expression, the name of a data file enclosed in quotes, or a pair (**plot**) or triple (**splot**) of mathematical expressions in the case of parametric functions. User-defined functions and variables may also be defined here.

plot and **splot** commands can be as simple as

```
plot sin(x)
```

and

```
splot x * y
```

or as complex as (!)

```
plot [t=1:10] [-pi:pi*2] tan(t),"data.1" with lines,t**2 with points
```

12.1 Data-file

Discrete data contained in a file can displayed by specifying the name of the data file (enclosed in quotes) on the **plot** or **splot** command line. Data files should contain one data point per line. Lines beginning with # (or ! on VMS) will be treated as comments and ignored. For **plot**s, each data point represents an (x,y) pair. For **splot**s, each point is an (x,y,z) triple. For **plot**s with error bars (see **plot errorbars**), each data point is either (x,y,ydelta) or (x,y,ylow,yhigh). In all cases, the numbers on each line of a data file must be separated by blank space. This blank space divides each line into columns.

For **plot**s the x value may be omitted, and for **splot**s the x and y values may be omitted. In either case the omitted values are assigned the current coordinate number. Coordinate numbers start at 0 and are incremented for each data point read.

To specify other formats, see **plot datafile using**.

In the **plot** command, blank lines in the data file cause a break in the plot. There will be no line drawn between the preceding and following points if the plot style is **lines** or **linespoints** (see **plot style**). This does not change the plot style, as would plotting the data as separate curves.

This example compares the data in the file population.dat to a theoretical curve:

```
pop(x) = 103*exp((1965-x)/10)
plot [1960:1990] 'population.dat', pop(x)
```

The file population.dat might contain:

```
# Gnu population in Antarctica since 1965
1965   103
1970   55
1975   34
1980   24
1985   10
```

When a data file is plotted, **samples** and **iso_samples** are ignored. Curves plotted using the **plot** command are automatically extended to hold the entire curve. Similarly grid data plotted using the **splot** command is automatically extended, using the assumption that isolines are separated by blank lines (a line with only a CR/LF in it).

Implicitly, there are two types of 3-d datafiles. If all the isolines are of the same length, the data is assumed to be a grid data, i.e., the data has a grid topology. Cross isolines in the other parametric direction (the ith cross isoline passes thru the ith point of all the provided isolines) will also be drawn for grid data. (Note contouring is available for grid data only.) If all the isolines are not of the same length, no cross isolines will be drawn and contouring that data is impossible.

For splot if 3-d datafile and using format (see **splot datafile using**) specify only z (height field), a non parametric mode must be specified. If, on the other hand, x, y, and z are all specified, a parametric mode should be selected (see **set parametric**) since data is defining a parametric surface.

A simple example of plotting a 3-d data file is

```
set parametric
splot 'glass.dat'
```

or

```
set noparametric
splot 'datafile.dat'
```

where the file datafile.dat might contain:

```
# The valley of the Gnu.
10
10
10

10
5
10

10
1
10

10
0
10
```

Note datafile.dat defines a 4 by 3 grid (4 rows of 3 points each). Rows are separated by blank lines.

On some computer systems with a popen function (UNIX), the datafile can be piped through a shell command by starting the file name with a '<'. For example:

```
pop(x) = 103*exp(x/10)
plot '< awk "{print $1-1965 $2}" population.dat', pop(x)
```

would plot the same information as the first population example but with years since 1965 as the x axis.

For more information about 3-d plotting, see **splot**.

12.1.1 Using

The format of data within a file can be selected with the **using** option. An explicit scanf string can be used, or simpler column choices can be made.

Syntax:

```
plot "datafile" { using { <ycol> |
                          <xcol>:<ycol> |
                          <xcol>:<ycol>:<ydelta> |
                          <xcol>:<ylow>:<yhigh> }
                        {"<scanf string>"} } ...
```

and

```
splot "datafile" { using { <xcol>:<ycol>:<zcol> | <zcol> }
                         {"<scanf string>"} } ...
```

<xcol>, <ycol>, and <zcol> explicitly select the columns to plot from a space or tab separated multi-column data file. If only <ycol> is selected for **plot**, <xcol> defaults to 1. If only <zcol> is selected for **splot**, then only that column is read from the file. An <xcol> of 0 forces <ycol> to be plotted versus its coordinate number. <xcol>, <ycol>, and <zcol> can be entered as constants or expressions.

If errorbars (see also **plot errorbars**) are used for **plot**s, ydelta (for example, a +/- error) should be provided as the third column, or ylow and yhigh as third and fourth columns. These columns must follow the x and y columns.

Scanf strings override any <xcol>:<ycol>(:<zcol>) choices, except for ordering of input, e.g.,

```
plot "datafile" using 2:1 "%f%*f%f"
```

causes the first column to be y and the third column to be x.

If the scanf string is omitted, the default is generated based on the <xcol>:<ycol>(:<zcol>) choices. If the **using** option is omitted, "%f%f" is used for **plot** ("%f%f%f%f" for **errorbar plot**s) and "%f%f%f" is used for **splot**.

Examples:

```
plot "MyData" using "%*f%f%*20[^\n]%f" with lines
```

Data are read from the file "MyData" using the format "%*f%f%*20[^\n]%f". The meaning of this format is: "%*f" ignore the first number, "%f" then read in the second and assign to x, "%*20[^\n]" then ignore 20 non-newline characters, "%f" then read in the y value.

```
n=3;
plot "MyData", "MyData" using n
```

causes GNUPLOT to plot the second and third columns of MyData versus the first column. The command 'n=4; replot' would then plot the second and fourth columns of MyData versus the first column.

```
splot "glass.dat" using 1
```

causes GNUPLOT to plot the first coordinate of the points of glass.dat as the z coordinate while ignoring the other two coordinates.

Note: GNUPLOT first reads a line of the data file into a buffer and then does a

```
sscanf(input_buffer, scanf_string, &x, &y{, &z});
```

where 'x', 'y', and 'z' are of type 'float'. Any scanf string that specifies two (three for **splot**, three or four for **errorbars**) float numbers may be used.

12.2 Errorbars

Error bars are supported for 2-d data file plots by reading one or two additional columns specifying ydelta or ylow and yhigh respectively. No support exists for x error bars or any error bars for **splot**s.

In the default situation, GNUPLOT expects to see three or four numbers on each line of the data file, either (x, y, ydelta) or (x, y, ylow, yhigh). The x coordinate must be specified. The order of the numbers must be exactly as given above. Data files in this format can easily be plotted with error bars:

```
plot "data.dat" with errorbars
```

The error bar is a vertical line plotted from (x, ylow) to (x, yhigh). If ydelta is specified instead of ylow and yhigh, ylow=y-ydelta and yhigh=y+ydelta are derived. If there are only two numbers on the line, yhigh and ylow are both set to y. To get lines plotted between the data points, **plot** the data file twice, once with errorbars and once with lines.

If y autoscaling is on, the y range will be adjusted to fit the error bars.

The **using** option may be used to specify how columns of the data file are to be assigned to x, y, ydelta, ylow, and yhigh. The x column must be provided and both the x and y columns must appear before the errorbar columns. If three column numbers are given, they are x, y, and ydelta. If four columns are given, they are x, y, ylow, and yhigh.

Examples:

```
plot "data.dat" using 1:2:3:4 with errorbars
plot "data.dat" using 3:2:6 with errorbars
plot "data.dat" using 3:4:8:7 with errorbars
```

The first example reads, x, y, ylow, and yhigh, from columns 1, 2, 3, and 4. This is equivalent to the default. The second example reads x from the third column, y from second and ydelta from the sixth column. The third example reads x from the third column, y from the fourth, ylow from the eighth, and yhigh from seventh columns.

See also **plot using** and **plot style**.

12.3 Parametric

When in parametric mode (**set parametric**) mathematical expressions must be given in pairs for **plot** and in triplets for **splot**:

```
plot sin(t),t**2
```

or

```
splot cos(u)*cos(v),cos(u)*sin(v),sin(u)
```

Data files are plotted as before, except any preceding parametric function must be fully specified before a data file is given as a plot. In other words, the x parametric function (sin(t) above) and the y parametric function (t**2 above) must not be interrupted with any modifiers or data functions; doing so will generate a syntax error stating that the parametric function is not fully specified.

Ranges take on a different meaning when in parametric mode. The first range on the **plot** command is the **trange**, the next is the **xrange**, and the last is the **yrange**. For **splot** the order is **urange**, **vrange**, **xrange**, **yrange**, and finally **zrange**. The following **plot** command shows setting the **trange** to [-pi:pi], the **xrange** to [-1.3:1.3] and the **yrange** to [-1:1] for the duration of the plot:

```
plot [-pi:pi] [-1.3:1.3] [-1:1] sin(t),t**2
```

Other modifiers, such as **with** and **title**, may be specified only after the parametric function has been completed:

```
plot sin(t),t**2 title 'Parametric example' with linespoints
```

12.4 Ranges

The optional range specifies the region of the plot that will be displayed.

Ranges may be provided on the **plot** and **splot** command line and affect only that plot, or in the **set xrange**, **set yrange**, etc., commands, to change the default ranges for future plots.

Syntax:

```
[{<dummy-var> =} {<xmin> : <xmax>}] { [{<ymin> : <ymax>}] }
```

where <dummy-var> is the independent variable (the defaults are x and y, but this may be changed with **set dummy**) and the min and max terms can be constant expressions.

Both the min and max terms are optional. The ':' is also optional if neither a min nor a max term is specified. This allows '[ ]' to be used as a null range specification.

Specifying a range in the **plot** command line turns autoscaling for that axis off for that plot. Using one of the **set** range commands turns autoscaling off for that axis for future plots, unless changed later. (See **set autoscale**).

Examples:

This uses the current ranges:

```
plot cos(x)
```

This sets the x range only:

```
plot [-10:30] sin(pi*x)/(pi*x)
```

This is the same, but uses t as the dummy-variable:

```
plot [t = -10 :30]  sin(pi*t)/(pi*t)
```

This sets both the x and y ranges:

```
plot [-pi:pi] [-3:3]  tan(x), 1/x
```

This sets only the y range, and turns off autoscaling on both axes:

```
plot [ ] [-2:sin(5)*-8] sin(x)**besj0(x)
```

This sets xmax and ymin only:

```
plot [:200] [-pi:]  exp(sin(x))
```

This sets the x, y, and z ranges:

```
splot [0:3] [1:4] [-1:1] x*y
```

12.5 Style

Plots may be displayed in one of six styles: **lines**, **points**, **linespoints**, **impulses**, **dots**, or **errorbars**. The **lines** style connects adjacent points with lines. The **points** style displays a small symbol at each point. The **linespoints** style does both **lines** and **points**. The **impulses** style displays a vertical line from the x axis (or from the grid base for **splot**) to each point. The **dots** style plots a tiny dot at each point; this is useful for scatter plots with many points.

The **errorbars** style is only relevant to 2-d data file plotting. It is treated like **points** for **splot**s and function **plot**s. For data **plot**s, **errorbars** is like **points**, except that a vertical error bar is also drawn: for each point (x,y), a line is drawn from (x,ylow) to (x,yhigh). A tic mark is placed at the ends of the error bar. The ylow and yhigh values are read from the data file's columns, as specified with the **using** option to plot. See **plot errorbars** for more information.

Default styles are chosen with the **set function style** and **set data style** commands.

By default, each function and data file will use a different line type and point type, up to the maximum number of available types. All terminal drivers support at least six different point types, and re-use them, in order, if more than six are required. The LaTeX driver supplies an additional six point types (all variants of a circle), and thus will only repeat after twelve curves are plotted with points.

If desired, the style and (optionally) the line type and point type used for a curve can be specified.

Syntax:

```
with <style> {<linetype> {<pointtype>}}
```

where <style> is either **lines**, **points**, **linespoints**, **impulses**, **dots**, or **errorbars**. The <linetype> and <pointtype> are positive integer constants or expressions and specify the line type and point type to be used for the plot. Line type 1 is the first line type used by default, line type 2 is the second line type used by default, etc.

Examples:

This plots sin(x) with impulses:

```
plot sin(x) with impulses
```

This plots x*y with points, x**2 + y**2 default:

```
splot x*y w points, x**2 + y**2
```

This plots tan(x) with the default function style, "data.1" with lines:

```
plot [ ] [-2:5] tan(x), "data.1" with l
```

This plots "leastsq.dat" with impulses:

```
plot 'leastsq.dat' w i
```

This plots "exper.dat" with errorbars and lines connecting the points:

```
plot 'exper.dat' w lines, 'exper.dat' w errorbars
```

Here 'exper.dat' should have three or four data columns.

This plots x**2 + y**2 and x**2 - y**2 with the same line type:

```
splot x**2 + y**2 with line 1, x**2 - y**2 with line 1
```

This plots sin(x) and cos(x) with linespoints, using the same line type but different point types:

```
plot sin(x) with linesp 1 3, cos(x) with linesp 1 4
```

This plots file "data" with points style 3:

```
plot "data" with points 1 3
```

Note that the line style must be specified when specifying the point style, even when it is irrelevant. Here the line style is 1 and the point style is 3, and the line style is irrelevant.

See **set style** to change the default styles.

12.6 Title

A title of each plot appears in the key. By default the title is the function or file name as it appears on the plot command line. The title can be changed by using the **title** option. This option should precede any **with** option.

Syntax:

```
title "<title>"
```

where <title> is the new title of the plot and must be enclosed in quotes. The quotes will not be shown in the key.

Examples:

This plots y=x with the title 'x':

```
plot x
```

This plots the "glass.dat" file with the title 'surface of revolution':

```
splot "glass.dat" title 'surface of revolution'
```

This plots x squared with title "x^2" and "data.1" with title 'measured data':

```
plot x**2 title "x^2", "data.1" t 'measured data'
```

13 Print

The **print** command prints the value of <expression> to the screen.

Syntax:

```
print <expression>
```

See **expressions**.

14 Pwd

The **pwd** command prints the name of the working directory to the screen.

Syntax:

```
pwd
```

15 Quit

The **exit** and **quit** commands and END-OF-FILE character will exit GNUPLOT. All these commands will clear the output device (as the **clear** command does) before exiting.

16 Replot

The **replot** command without arguments repeats the last **plot** or **splot** command. This can be useful for viewing a plot with different **set** options, or when generating the same plot for several devices.

Arguments specified after a **replot** command will be added onto the last **plot** (**splot**) command (with an implied ',' separator) before it is repeated. **replot** accepts the same arguments as the **plot** (**splot**) commands except that ranges cannot be specified. See **command-line editing** for ways to edit the last **plot** (**splot**) command.

17 Save

The **save** command saves user-defined functions, variables, set options or all three plus the last **plot** (**splot**) command to the specified file.

Syntax:

```
save  {<option>} "<filename>"
```

where <option> is **functions**, **variables** or **set**. If no option is used, GNUPLOT saves functions, variables, set options and the last **plot** (**splot**) command.

saved files are written in text format and may be read by the **load** command.

The filename must be enclosed in quotes.

Examples:

```
save "work.gnu"
save functions 'func.dat'
save var 'var.dat'
save set "options.dat"
```

18 Set-show

The **set** command sets LOTS of options.

The **show** command shows their settings. **show all** shows all the settings.

18.1 Angles

By default, GNUPLOT assumes the independent variable in polar plots is in units of radians. If **set angles degrees** is specified before **set polar** then the default range is [0:360] and the independent variable has units of degrees. This is particularly useful for plots of data files. The angle setting also hold for the 3-d mapping as set via the **set mapping** command.

Syntax:

```
set angles { degrees | radians }
show angles
```

18.2 Arrow

Arbitrary arrows can be placed on a plot using the **set arrow** command.

Syntax:

```
set arrow {<tag>} {from <sx>,<sy>{,<sz>}}
                  {to <ex>,<ey>{,<ez>}} {{no}head}
set noarrow {<tag>}
show arrow
```

Unspecified coordinates default to 0. The x, y, and z values are in the graph's coordinate system. The z coordinate is only used in **splot** commands. <tag> is an integer that identifies the arrow. If no tag is given, the lowest unused tag value is assigned automatically. The tag can be used to delete or change a specific arrow. To change any attribute of an existing arrow, use the **set arrow** command with the appropriate tag, and specify the parts of the arrow to be changed. Specifying nohead requests the arrow be drawn without a head (yielding a line segment). By default, arrows have heads.

Arrows outside the plotted boundaries are permitted but may cause device errors.

Examples:

To set an arrow pointing from the origin to (1,2), use:

```
set arrow to 1,2
```

To set an arrow from (-10,4,2) to (-5,5,3), and tag the arrow number 3, use:

```
set arrow 3 from -10,4,2 to -5,5,3
```

To change the preceding arrow begin at 1,1,1, without an arrow head, use:

```
set arrow 3 from 1,1,1 nohead
```

To delete arrow number 2 use:

```
set noarrow 2
```

To delete all arrows use:

```
set noarrow
```

To show all arrows (in tag order) use:

```
show arrow
```

18.3 Autoscale

Auto scaling may be set individually on the x, y or z axis or globally on all axes. The default is to autoscale all axes.

When autoscaling, the plot range is automatically computed and the dependent axis (y for a **plot** and z for **splot**) is scaled to include the range of the function or data being plotted.

If autoscaling of the dependent axis (y or z) is not set, the current y or z range is used.

See **set yrange** or **set zrange**.

Autoscaling the independent variables (x for **plot** and x,y for **splot**) is a request to set the domain to match any data file being plotted. If there are no data files then autoscaling an independent variable has no effect. In other words, in the absence of a data file, functions alone do not affect the x range (or the y range if plotting z = f(x,y)).

See **set xrange**, or **set yrange**.

The behavior of autoscaling remains consistent in parametric mode, however, there are more dependent variables and hence more control over x, y, and z plot scales. In parametric mode, the independent or dummy variable is t for **plot**s and u,v for **splot**s. Autoscale in parametric mode, then, controls all ranges (t, u, v, x, y, and z) and allows x, y, and z to be fully autoscaled.

See **set parametric**.

Syntax:

```
set autoscale <axes>
set noautoscale <axes>
show autoscale
```

where <axes> is either **x**, **y**, **z** or **xy**. If <axes> is not given then all axes are assumed.

Examples:

This sets autoscaling of the y axis. x axis autoscaling is not affected.

```
set autoscale y
```

This sets autoscaling of the x and y axes.

```
set autoscale xy
```

This sets autoscaling of the x, y and z axes.

```
set autoscale
```

This disables autoscaling of the x, y and z axes.

```
set noautoscale
```

This disables autoscaling of the z axis only.

```
set noautoscale z
```

18.3.1 Parametric mode

When in parametric mode (**set parametric**) the xrange is as fully scalable as the yrange. In other words, in parametric mode the x axis can be automatically scaled to fit the range of the parametric function that is being plotted. Of course, the y axis can also be automatically scaled just as in the non-parametric case. If autoscaling on the x axis is not set, the current x range is used.

When there is a mix of data files and functions, the xrange of the functions is selected as that of the data files if autoscale is true for x. While this keeps the behavior compatible with non-parametric plotting, it may not be retained in the future. The problem is that, in parametric mode, the x and y ranges are not as distinguishable as in the non-parametric mode and this behavior may not be the most useful.

For completeness a last command **set autoscale t** is accepted. However, the effect of this "scaling" is very minor. When GNUPLOT determines that the t range would be empty it makes a small adjustment if autoscaling is true. Otherwise, GNUPLOT gives an error. Such behavior may, in fact, not be very useful and the command **set autoscale t** is certainly questionable.

splot extends the above idea similarly. If autoscaling is set then x, y, and z ranges are computed and each axis scaled to fit the resulting data.

18.4 Border

The **set border** and **set noborder** commands controls the display of the plot borders for the **plot** and **splot** commands.

Syntax:

```
set border
set noborder
show border
```

18.5 Clip

GNUPLOT can clip data points and lines that are near the boundaries of a plot.

Syntax:

```
set clip <clip-type>
set noclip <clip-type>
show clip
```

Three clip types are supported by GNUPLOT: **points**, **one**, and **two**. One, two, or all three clip types may be active for a single plot.

The **points** clip type forces GNUPLOT to clip (actually, not plot at all) data points that fall within but too close to the boundaries (this is so the large symbols used for points will not extend outside the boundary lines). Without clipping points near the boundaries may look bad; try adjusting the x and y ranges.

Setting the **one** clip type causes GNUPLOT to plot the line segments which have only one of the two endpoints with the plotting region. Only the in-range portion of the line is drawn. The alternative is to not draw any portion of the line segment.

Some lines may have both endpoints out of range, but pass through the plotting area. Setting the **two** clip-type allows the visible portion of these lines to be drawn.

In no case is a line drawn outside the plotting area.

The defaults are **noclip points**, **clip one**, and **noclip two**.

To check the state of all forms of clipping, use

```
show clip
```

For backward compatibility with older versions, the following forms are also permitted.

```
set clip
set noclip
```

set clip is synonymous with **set clip points**. **set noclip** turns off all three types of clipping.

18.6 Cntrparam

Sets the different parameters for the contouring plot (see also **contour**).

Syntax:

```
set cntrparam { { linear | cubicspline | bspline } |
                points <n> |
                levels <n> |
                order <n> }
```

This command controls the way contours are plotted. <n> should be an integral constant expression. The parameters are:

linear, **cubicspline**, **bspline** - Controls type of approximation or interpolation. If **linear**, then the contours are drawn piecewise linear, as extracted from the surface directly. If **cubicspline**, then piecewise linear contours are interpolated to form a somewhat smoother contours, but which may undulate. The third option is the uniform **bspline**, which only approximates the piecewise linear data but is guaranteed to be smoother.

points - Eventually all drawings are done with piecewise linear strokes. This number controls the number of points used to approximate a curve. Relevant for **cubicspline** and **bspline** modes only.

levels - Number of contour levels. If the surface is bounded by zmin and zmax then contours will be generated from zmin+dz to zmax-dz in steps of size dz, where dz = (zmax - zmin) / (levels + 1).

order - Order of the bspline approximation to be used. The bigger this order is, the smoother the resulting contour. (Of course, higher order bspline curves will move further away from the original peicewise linear data.) This option is relevant for **bspline** mode only. Allowed values are integers in the range from 2 (linear) to 10.

18.7 Contour

Enable contour drawing for surfaces. This option is available for **splot** only.

Syntax:

```
set contour { base | surface | both }
set nocontour
```

If no option is provided to **set contour**, the default is **base**. The three options specify where to draw the contours: **base** draws the contours on the grid base where the x/ytics are placed, **surface** draws the contours on the surfaces themselves, and **both** draws the contours on both the base and the surface.

See also **set cntrparam** for the parameters that affect the drawing of contours.

18.8 Data style

The **set data style** command changes the default plotting style for data plots.

Syntax:

```
set data style
show data style
set data style <style-choice>
```

In the first case, **set data style** returns the possible style choices: **lines**, **points**, **linespoints**, **dots**, **impulses**, or **errorbars**. **show data style** shows the current default plotting style for data. **set data style dots** would actually change the default plotting style. See also **plot**.

18.9 Dummy

By default, GNUPLOT assumes that the independent variable for the **plot** command is x, and the independent variables for the **splot** command are x and y. They are called the dummy variables because it is just a notation to indicate the independent variables. The **set dummy** command changes these default dummy variable names. For example, it may be more convenient to call the dummy variable t when plotting time functions:

```
set dummy t
plot sin(t), cos(t)
```

Syntax:

```
set dummy <dummy-var>{,<dummy-var>}
show dummy
```

Examples:

```
set dummy u,v
set dummy ,s
```

to set both dummy variables to u and v or set only the second variable to s.

The **set parametric** command also changes the dummy variables (to t for **plot** and u,v for **splot**s).

18.10 Format

The format of the tic-mark labels can be set with the **set format** command. The default format for both axes is "%g", but other formats such as "%.2f" or "%3.0fm" are often desirable. Anything accepted by printf when given a double precision number, and then accepted by the terminal, will work. In particular, the formats f, e, and g will work, and the d, o, x, c, s, and u formats will not work.

Syntax:

```
set format {<axes>} {"<format-string>"}
show format
```

where <axes> is either **x**, **y**, **z**, **xy**, or nothing (which is the same as **xy**). The length of the string representing a ticmark (after formatting with printf) is restricted to 100 characters. If the format string is omitted, the format will be returned to the default "%g". For LaTeX users, the format "$%g$" is often desirable. If the empty string "" is used, no label will be plotted with each tic, though the tic mark will still be plotted. To eliminate all tic marks, use **set noxtics** or **set noytics**.

See also **set xtics** and **set ytics** for more control over tic labels.

18.11 Function style

The **set function style** command changes the default plotting style for functions.

Syntax:

```
set function style
show function style
set function style <style-choice>
```

In the first case, **set function style** returns the possible style choices: **lines**, **points**, **linespoints**, **dots**, **impulses**, or **errorbars**. **show function style** shows the current default plotting style for functions. **set function style linespoints** would actually change the default plotting style. See also **plot**.

18.12 Functions

The **show functions** command lists all user-defined functions and their definitions.

Syntax:

```
show functions
```

18.13 Grid

The optional **set grid** draws a grid at the tic marks with the axis linetype.

Syntax:

```
set grid
set nogrid
show grid
```

18.14 Hidden3d

The **set hidden3d** command enables hidden line removal for explicit surface plotting (see **splot**). Hidden line removal may be used for both explicit functions and for explicit data where gnuplot plot is in nonparametric mode (see **set parametric**).

When this flag is set both the surface hidden portion and possibly its hidden contours (see **set contour**) as well as the hidden grid will be removed. Labels and arrows are always visible and are unaffected by this command.

Each surface has its hidden part removed with respect to itself, if more than one surface is ploted. This mode is meaningfull when surfaces are plotted using line style drawing only.

Syntax:

```
set hidden3d
set nohidden3d
show hidden3d
```

18.15 Isosamples

An isoline is a curve parametrized by one of the surface parameters while the other surface parameter is fixed. Isolines are a simple means to display a surface. By fixing the u parameter of surface s(u,v), the iso-u lines of the form c(v) = s(u0,v) are produced, and by fixing the v parameter, the iso-v lines of the form c(u) = s(u,v0) are produced.

The isoline density of surfaces may be changed by the **set isosamples** command. By default, sampling is set to 10 isolines per u or v axis. A higher sampling rate will produce more accurate plots, but will take longer. This parameter has no effect on data file plotting.

Syntax:

```
set isosamples <expression>
show isosamples
```

18.16 Key

The **set key** enables a key describing curves on a plot. By default the key is placed in the upper right corner of the plot.

Syntax:

```
set key
set key <x>,<y>{,<z>}
set nokey
show key
```

The coordinates <x>, <y> (and <z> for **splot**s) specify the location of the key on the plot. The key is drawn as a sequence of lines, with one plot described on each line. On the right hand side of each line is a representation that attempts to mimic the way the curve is plotted. On the left side of each line is the text description, obtained from the **plot** command. See **plot title** to change this description. The lines are vertically arranged so an imaginary straight line divides the left- and right-hand sides of the key. It is the coordinates of this line that are specified with the **set key** command. In a **plot**, only the x and y coordinates are used to specify the line position. For a **splot**, x, y and z are all being used as a 3-d location mapped using the same mapping as the plot itself to form the required 2-d screen position of the imaginary line.

Some or all of the key may be outside of the plot boundary, although this may interfere with other labels and may cause an error on some devices.

Examples:

This places the key at the default location:

```
set key
```

This disables the key:

```
set nokey
```

This places a key at coordinates 2,3.5,2

```
set key 2,3.5,2
```

18.17 Label

Arbitrary labels can be placed on the plot using the **set label** command. If the z coordinate is given on a **plot** it is ignored; if it is missing on a **splot** it is assumed to be 0.

Syntax:

```
set label {<tag>} {"<label_text>"} {at <x>,<y>{,<z>}}
                  {<justification>}
set nolabel {<tag>}
show label
```

The text defaults to "", and the position to 0,0,0. The <x>, <y>, and <z> values are in the graph's coordinate system. The tag is an integer that is used to identify the label. If no <tag> is given, the lowest unused tag value is assigned automatically. The tag can be used to delete or change a specific label. To change any attribute of an existing label, use the **set label** command with the appropriate tag, and specify the parts of the label to be changed.

By default, the text is placed flush left against the point x,y,z. To adjust the way the label is positioned with respect to the point x,y,z, add the parameter <justification>, which may be **left**, **right** or **center**, indicating that the point is to be at the left, right or center of the text. Labels outside the plotted boundaries are permitted but may interfere with axes labels or other text.

Examples:

To set a label at (1,2) to "y=x" use:

```
set label "y=x" at 1,2
```

To set a label "y=x^2" with the right of the text at (2,3,4), and tag the label number 3, use:

```
set label 3 "y=x^2" at 2,3,4 right
```

To change the preceding label to center justification, use:

```
set label 3 center
```

To delete label number 2 use:

```
set nolabel 2
```

To delete all labels use:

```
set nolabel
```

To show all labels (in tag order) use:

```
show label
```

(The Latex, EEPIC, and Imagen drivers allow \\ in a string to specify a newline.)

18.18 Logscale

Log scaling may be set on the x, y, and z axes.

Syntax:

```
set logscale <axes>
set nologscale <axes>
show logscale
```

where <axes> may be any combinations of **x**, **y**, and **z**, in any order. If <axes> is not given then all three axes are assumed. The command **set logscale** turns on log scaling on the specified axes, while **set nologscale** turns off log scaling.

Examples:

To enable log scaling in both x and z axes:

```
set logscale xz
```

To disable z axis log scaling:

```
set nologscale z
```

18.19 Mapping

Syntax:

```
set mapping { cartesian | spherical | cylindrical }
```

Data for **splot**s are usually in regular Euclidean space and are provided in Cartesian coordinates. Such 3-d data require three coordinates (x, y and z) or one coordinate (only z) in each line in the data file. In order to be able to use spherical or cylindrical coordinate systems, use the **set mapping** command. In both cases two coordinates are expected in each line of the data. For a spherical coordinate system, these are theta and phi (in units as specified by **set angles**) and the mapping is:

```
x = cos( theta ) * cos( phi )
y = sin( theta ) * cos( phi )
z = sin( phi )
```

For a cylindrical coordinate system, the mapping uses two variables, theta (in units as specified by **set angles**) and z:

```
x = cos( theta )
y = sin( theta )
z = z
```

Again, note that mapping will affect data file **splot**s only.

18.20 Offsets

The amount of the graph that the plot takes up may be controlled to some extent with the **set offsets** command. This command takes four offset arguments: <left>, <right>, <top> and <bottom>. By default, each offset is 0. Each offset may be a constant or an expression. Left and right offsets are given in units of the x axis, while top and bottom offsets are given in units of the y axis. The plot of sin(x), displayed with offsets of 0, 0, 2, 2 will take up 1/3 of the displayed y axis. Offsets are particularly useful with polar coordinates as a means of compensating for aspect ratio distortion. Offsets are ignored in **splot**s.

Syntax:

```
set offsets <left>, <right>, <top>, <bottom>
show offsets
```

18.21 Output

By default, plots are displayed to the standard output. The **set output** command redirects the display to the specified file or device.

Syntax:

```
set output {"<filename>"}
show output
```

The filename must be enclosed in quotes. If the filename is omitted, output will be sent to the standard output.

On machines with popen functions (UNIX), output can be piped through a shell command if the first letter of the filename is '|'. For instance,

Syntax:

```
set output "|lpr -Plaser filename"
set output "|lp -dlaser filename"
```

(On MSDOS machines, set output "prn" will direct the output to the default printer.)

18.22 Parametric

The **set parametric** command changes the meaning of **plot** (**splot**) from normal functions to parametric functions. The command **set noparametric** changes the plotting style back to normal, single-valued expression plotting.

In 2-d plotting, a parametric function is determined by a pair of parametric functions operating on a parameter. An example of a 2-d parametric function would be plot sin(t),cos(t) (which defines a circle).

For 3-d plotting, the surface is described as x=f(u,v), y=g(u,v), z=h(u,v). Therefore a triplet of functions are required. An example of 3-d parametric function would be cos(u)*cos(v),cos(u)*sin(v),sin(u) (which defines a sphere). It takes three parametric function specifications in terms of the parametric dummy arguments to describe a single graph.

The total set of possible plots is a superset of the simple f(x) style plots, since the two (three) functions can describe the x and y (and z) values to be computed separately. In fact, plots of the type t,f(t) (u,v,f(u,v)) are equivalent to those produced with f(x) when the x values are computed using the identity function as the first function.

Note that the order the parametric functions are specified is xfunction, yfunction (and zfunction) and that each operates over the common parametric domain.

Also, the **set parametric** function implies a new range of values. Whereas the normal f(x) and f(x,y) style plotting assume an xrange and yrange (and zrange), the parametric mode additionally specifies a trange, urange, and vrange. These ranges may be set directly with **set trange**, **set urange** and **set vrange**, or by specifying the range on the **plot** or **splot** commands. Currently the default range for these parametric variables is [-5:5]. Setting the ranges to something more meaningful is expected.

18.23 Polar

The **set polar** command changes the meaning of the plot from rectangular coordinates to polar coordinates. In polar coordinates, the dummy variable (x) is an angle. The range of this angle is changed from whatever it was to [0:2*pi], or, if degree unit has been selected, to [0:360] (see **set angles**).

The command **set nopolar** changes the meaning of the plot back to the default rectangular coordinate system. The range of x is changed from whatever it was to [-10:10].

The **set polar** command is not supported for **splot**s. See the **set mapping** command for similar functionality for **splot**s.

While in polar coordinates the meaning of an expression in x is really r = f(x), where x is an angle of rotation. The xrange controls the domain (the angle) of the function, and the yrange controls the range (the radius). The plot is plotted in a rectangular box, and the x and y axes are both in units of the radius. Thus, the yrange controls both dimensions of the plot output. The tics and units are written along the axes rather than at the left and bottom. These unit are offset by <rmin> specified by the **rrange** (See **set rrange**). It is not possible to specify different output dimensions in the x or y directions. The yrange can be used to shift the plot diagonally to display only the first or third quadrants.

Syntax:

```
set polar
set nopolar
show polar
```

Example:

```
set polar
plot x*sin(x)
plot [-2*pi:2*pi] [-3:3] x*sin(x)
```

The first plot uses the default polar angular domain of 0 to 2*pi. The radius (and the size of the plot) is scaled automatically. The second plot expands the domain, and restricts the range of the radius (and the size of the plot) to [-3:3].

18.24 Rrange

The **set rrange** command sets the radial range used to compute x and y values when in polar mode. If not in polar mode (see **set polar**) then this range is not used. Use of this command offsets the polar singularity to the <rmin> value and shifts the units on the axes tic marks. For instance, **set rrange [-40:40]** would set the origin to -40 and would plot values of radial values between -40 to 40. Thus, if 360 degrees of data were plotted, then the plot would extend 80 units in radially from the origin. To view the entire plot, a **set yrange [-80:80]** command would create a square viewport with a circular plot tangent at the axes. Because **xrange** is used specify the angular extent, only a square viewport can be specified by **yrange**. For instance, **set yrange [0:80]** would display the first quadrant and **set yrange [-80:0]** would display the third quadrant. Any square viewport of any size can be specified but it is constrained to be centered on a 45 degree line.

This range may also be specified on the **plot** command line when in polar mode.

Syntax:

```
set rrange [{<rmin> : <rmax>}]
```

where <rmin> and <rmax> terms are constants or expressions.

Both the <rmin> and <rmax> terms are optional. Anything omitted will not be changed, so

```
set rrange [:10]
```

changes rmax to 10 without affecting rmin.

18.25 Samples

The sampling rate of functions may be changed by the **set samples** command. By default, sampling is set to 100 points. A higher sampling rate will produce more accurate plots, but will take longer. This parameter no longer has any effect on data-file plotting.

Syntax:

```
set samples <expression>
show samples
```

18.26 Size

The **set size** command scales the displayed size of the plot. On some terminals, changing the size of the plot will result in text being misplaced. Increasing the size of the plot may produce strange results. Decreasing is safer.

Syntax:

```
set size {<xscale>,<yscale>}
show size
```

The <xscale> and <yscale> values are the scaling factors for the size. The defaults (1,1) are selected if the scaling factors are omitted.

Examples:

To set the size to normal size use:

```
set size
```

To make the plot half size use:

```
set size 0.5,0.5
```

To make a landscape plot have a 1:1 aspect ratio in polar mode use:

```
set size 0.721,1.0
```

To show the size use:

```
show size
```

For the LaTeX and Fig terminals the default size (scale factor 1,1) is 5 inches wide by 3 inches high. The big Fig terminal (**bfig**) is 7 inches wide by 5 inches high. The postscript default is landscape mode 10 inches wide and 7 inches high. Note that the size of the plot includes the space used by the labels; the plotting area itself is smaller.

18.27 Style

Plots may be displayed in one of six styles: **lines**, **points**, **linespoints**, **impulses**, **dots**, or **errorbars**. The **lines** style connects adjacent points with lines. The **points** style displays a small symbol at each point. The **linespoints** style does both **lines** and **points**. The **impulses** style displays a vertical line from the x axis to each point. The **dots** style plots a tiny dot at each data point; this is useful for scatter plots with many points.

The **errorbars** style is relevant only for to data file **plot**s. It is treated like **points** for function **plot**s and **splot**s. For data file **plot**s, **errorbars** is like **points**, except that a vertical error bar is also drawn: for each point (x,y), a line is drawn from (x,ylow) to (x,yhigh). A tic mark is placed at the ends of the error bar. The ylow and yhigh values are read from the data file's third and fourth columns, or as specified with the **using** option to plot. See **plot errorbars** for more information.

Default styles are chosen with the **set function style** and **set data style** commands. See **plot style** for information about how to override the default plotting style for individual functions.

Syntax:

```
set function style <style>
set data style <style>
show function style
show data style
```

where <style> is **lines**, **points**, **linespoints**, **impulses**, **dots**, or **errorbars**.

18.28 Surface

set surface controls the display of surfaces. It is useful if contours are to be displayed by themselves. Whenever **set nosurface** is issued, no surface isolines/mesh will be drawn. See also **set contour**.

Syntax:

```
set surface
set nosurface
show surface
```

18.29 Terminal

GNUPLOT supports many different graphics devices. Use the **set terminal** command to select the type of device for which GNUPLOT will produce output.

Syntax:

```
set terminal {<terminal-type>}
show terminal
```

If <terminal-type> is omitted, GNUPLOT will list the available terminal types. <terminal-type> may be abbreviated.

Use **set output** to redirect this output to a file or device.

Several terminals have additional options. For example, see **dumb**, **iris4d**, **hpljii** or **postscript**.

18.29.1 Dumb

The dumb terminal driver has an optional size specification.

Syntax:

```
set terminal dumb {<xsize> <ysize>}
```

where <xsize> and <ysize> set the size of the dumb terminals. Default is 79 by 24.

Examples:

```
set term dumb
set term dumb 79 49 #(VGA screen - why would anyone want to do that!?)
```

18.29.2 Hpljii

The HP LaserJet II and HP DeskJet drivers have a single option.

Syntax:

```
set terminal hpljii {<resolution>}
set terminal hpdj   {<resolution>}
```

where <resolution> is the resolution of the output in dots per inch. It must be **75**, **100**, **150** or **300**.

Example:

```
set terminal hpljii 150
```

18.29.3 Iris4d

The iris4d driver can operate in two modes.

Syntax:

```
set terminal iris4d {24}
```

If the hardware supports only 8 bits, use the default **set terminal iris4d**. If, however, the hardware supports 24 bits (8 per red/green/blue), use **set terminal iris4d 24**.

When using 24-bit mode, the colors can be directly specified via the file .gnuplot_iris4d that is searched in the current directory and then in the home directory specified by the HOME environment variable.

This file holds RGB values for the background, border, labels and nine plotting colors, in that order. For example, here is a file containing the default colors:

```
85   85   85     /* Back Ground */
0    0    0      /* Boundary */
170  0    170    /* Labeling */
85   255  255    /* Plot Color 1 */
170  0    0      /* Plot Color 2 */
0    170  0      /* Plot Color 3 */
255  85   255    /* Plot Color 4 */
255  255  85     /* Plot Color 5 */
255  85   85     /* Plot Color 6 */
85   255  85     /* Plot Color 7 */
0    170  170    /* Plot Color 8 */
170  170  0      /* Plot Color 9 */
```

This file has exactly 12 lines of RGB triples. No empty lines are allowed and anything after the third number in line is ignored.

18.29.4 Pbm

Several options may be set in the PBMplus driver.

Syntax:

```
set terminal pbm {<fontsize>}
set terminal pgm {<fontsize>}
set terminal ppm {<fontsize>}
```

where <fontsize> is **small**, **medium**, or **large**. Default size is 640 pixels wide and 480 pixels high. The pbm output is a portable bitmap (one bit per pixel). The pgm output is a portable graymap (three bits per pixel). The ppm output is a portable pixmap (color, four bits per pixel). The output of these drivers can be used with Jef Poskanzer's excellent PBMPLUS package which provides programs to convert the above PBMPLUS formats to GIF, TIFF, MacPaint, Macintosh PICT, PCX, X11 bitmap and many others.

Examples:

```
set term pbm small
set size 2,2
set term ppm medium
```

18.29.5 Postscript

Several options may be set in the PostScript driver.

Syntax:

```
set terminal postscript {<mode>} {<color>}
                        {"<fontname>"} {<fontsize>}
```

where <mode> is **landscape**, **portrait**, **eps** or **default**. Selecting default sets all options to their defaults. <color> is either **color** or **monochrome**. "<fontname>" is the name of a valid PostScript font. <fontsize> is the size of the font in PostScript points, before scaling by the **set size** command. Defaults

are **landscape**, **monochrome**, "Courier", and 14pt. Default size of PostScript plot is landscape mode 10 inches wide and 7 inches high.

To get EPS output, use the **eps** mode and make only one plot per file. In **eps** mode the whole plot is halved in size; the fonts are half the given size, and the plot is 5 inches wide and 3.5 inches high.

Examples:

```
set term postscript default       # old postscript
set term postscript landscape 22  # old psbig
set term postscript eps 14   # old epsf1
set term postscript eps 22   # old epsf2
set size 0.7,1.4
set term post portrait color "Times-Roman" 14
```

18.29.6 Aifm

Several options may be set in the Adobe Illustrator 3.0 driver.

Syntax:

```
set terminal aifm {<color>}
                          {"<fontname>"} {<fontsize>}
```

Selecting default sets all options to their defaults. <color> is either **color** or **monochrome**. "<fontname>" is the name of a valid PostScript font. <fontsize> is the size of the font in PostScript points, before scaling by the **set size** command. Defaults are **monochrome**, "Courier", and 14pt.

Also, since AI does not really support multiple pages, multiple graphs will be output directly on one another. However, each graph will be grouped individually, making it easy to separate them inside AI (just pick them up and move them).

Examples:

```
set term aifm
set term aifm 22
set size 0.7,1.4
set term aifm color "Times-Roman" 14
```

18.29.7 Table

Instead of producing a picture, term type 'table' prints out the evaluation results in a multicolumn ASCII table of X Y Z values. For those times when you really want to see the numbers, now you can see them on the screen or save to a file.

18.30 Tics

By default, tics are drawn inwards from the border on all four sides. The **set tics** command can be used to change the tics to be drawn outwards on the left and bottom borders only. This is useful when doing impulse plots.

Syntax:

```
set tics {<direction>}
show tics
```

where <direction> may be **in** or **out**. **set tics** defaults to **in**.

See also the **set xtics**, **set ytics**, and **set ztics** command for more control of tic marks. Using splot, in 3-d plots, one can adjust the relative height of the vertical (Z) axis using **set ticslevel**. The numeric argument provided specifies the location of the bottom of the scale. a zero will put it on the bottom grid and any positive number somewhere along the z axis.

Syntax:

```
set ticslevel {<level>}
show tics
```

where <level> is a non negative numeric argument. For example,

```
set ticslevel 0.5
```

sets the tics level to the default value.

See also the **set view**.

18.31 Time

The optional **set time** places the time and date of the plot either at the top or bottom of the left margin. The exact location is device dependent.

Syntax:

```
set time {<xoff>}{,<yoff>}
set notime
show time
```

Specifying constants <xoff> or <yoff> as optional offsets for the time will move the time <xoff> or <yoff> character screen coordinates. For example,

```
set time ,-3
```

will change only the y offset of the time, moving the title down by roughly the height of three characters.

18.32 Title

The **set title** command produces a plot title that is centered at the top of the plot. Using the optional x,y screen offsets, the title can be placed anywhere on the plot. **set title** with no parameters clears the title.

Syntax:

```
set title {"<title-text>"} {<xoff>}{,<yoff>}
show title
```

Specifying constants <xoff> or <yoff> as optional offsets for the title will move the title <xoff> or <yoff> character screen coordinates. Note these are screen coordinates and not plot coordinates. For example,

```
set title ,-1
```

will change only the y offset of the title, moving the title down by roughly the height of one character.

(The Latex, EEPIC, and Imagen drivers allow \\ in a string to specify a newline.)

18.33 Trange

The **set trange** command sets the parametric range used to compute x and y values when in parametric mode. If not in parametric mode (see **set parametric**) then this range is not used. This command does not affect x/y autoscaling or x/y ranges.

This range may also be specified on the **plot** command line when in parametric mode.

Syntax:

```
set trange [{<tmin> : <tmax>}]
```

where <tmin> and <tmax> terms are constants or expressions.

Both the <tmin> and <tmax> terms are optional. Anything omitted will not be changed, so

```
set trange [:10]
```

changes tmax to 10 without affecting tmin. See also **set urange** and **set parametric**.

18.34 Urange

The **set urange** and **set vrange** commands sets the parametric ranges used to compute x, y, and z values when in **splot** parametric mode. If not in parametric mode (see **set parametric**) then these ranges are not used. This command does not affect x/y autoscaling or x/y ranges.

This range may also be specified on the **splot** command line when in parametric mode. See **plot** for more information

Syntax:

```
set urange [{<umin> : <umax>}]
```

where <umin> and <umax> terms are constants or expressions.

Both the <umin> and <umax> terms are optional. Anything omitted will not be changed, so

```
set urange [:10]
```

changes umax to 10 without affecting umin. See also **set trange**.

18.35 Variables

The **show variables** command lists all user-defined variables and their values.

Syntax:

```
show variables
```

18.36 View

The **set view** command sets the view point for **splot**s. This command controls the way the 3-d coordinates of the plot are mapped into the 2-d screen space. This command provides controls to both rotation and scaling of the plotted data but supports orthographic projections only.

Syntax:

```
set view <rot_x> {,{<rot_z>}{,{<scale>}{,<scale_z>}}}
show view
```

where <rot_x> and <rot_z> control the rotation angles (in degrees) along a virtual 3-d coordinate system aligned with the screen such that the screen horizontal axis is x, screen vertical axis is y, and the axis perpendicular to the screen is z. <rot_x> is bounded to the [0:180] range with a default of 60 degrees, while <rot_z> is bounded to the [0:360] range with a default of 30 degrees. <scale> controls the scaling of the entire **splot**, while <scale_z> scales the z axis only. Both scales default to 1.0.

Examples:

```
set view 60, 30, 1, 1
set view ,,0.5
```

The first sets all the four default values. The second changes only scale, to 0.5.

See also **set ticslevel**.

18.37 Vrange

The **set vrange** command is similar to the **set urange** command. Please see **set urange**.

18.38 Xlabel

The **set xlabel** command sets the x-axis label that is centered along the x axis. Using the optional x,y screen offsets, the label can be placed anywhere on the plot. **set xlabel** with no parameters clears the label.

Syntax:

```
set xlabel {"<label>"} {<xoff>}{,<yoff>}
show xlabel
```

Specifying constants <xoff> or <yoff> as optional offsets for the label will move the label <xoff> or <yoff> character screen coordinates. For example,

```
set xlabel -1
```

will change only the x offset of the xlabel, moving the label roughly one character width to the left.

(The LaTeX, EEPIC, and Imagen drivers allow \\ in a string to specify a newline.)

18.39 Xrange

The **set xrange** command sets the horizontal range that will be displayed. This command turns x axis autoscaling off.

This range may also be specified on the **plot** command line.

Syntax:

```
set xrange [{<xmin> : <xmax>}]
```

where <xmin> and <xmax> terms are constants or expressions.

Both the <xmin> and <xmax> terms are optional. Anything omitted will not be changed, so

```
set xrange [:10]
```

changes xmax to 10 without affecting xmin.

18.40 Xtics

Fine control of the x axis tic marks is possible with the **set xtics** command. The x-axis tic marks may be turned off with the **set noxtics** command. They may be turned on (the default state) with **set xtics**.

Syntax:

```
set xtics { {<start>, <incr>{, <end>}} |
            {({"<label>"} <pos> {, {"<label>"} <pos>}...)} }
set noxtics
show xtics
```

The <start>, <incr>, <end> form specifies that a series of tics will be plotted on the x axis between the x values <start> and <end> with an increment of <incr>. If <end> is not given it is assumed to be infinity. The increment may be negative. For example,

```
 set xtics 0,.5,10
```

makes tics at 0, 0.5, 1, 1.5, ..., 9.5, 10.

The ("<label>" <pos>, ...) form allows arbitrary tic positions or non-numeric tic labels. A set of tics are a set of positions, each with its own optional label. Note that the label is a string enclosed by quotes, and may be a constant string, such as "hello", or contain formatting information for the tic number (which is the same as the position), such as "%3f clients". See **set format** for more information about this case. The label may even be empty. Examples:

```
set xtics ("low" 0, "medium" 50, "high" 100)
set xtics (1,2,4,8,16,32,64,128,256,512,1024)
set xtics ("bottom" 0, "" 10, "top" 20)
```

Tics will only be plotted when in range.

The **set ytics** and **set noytics** commands work identically. See also the **set format** command.

18.41 Xzeroaxis

set xzeroaxis draws the x-axis. By default, this option is on. **set noxzeroaxis** causes GNUPLOT to omit the x-axis.

Syntax:

```
set xzeroaxis
set noxzeroaxis
show xzeroaxis
```

18.42 Ylabel

The **set ylabel** command sets the y-axis label. The position of this label depends on the terminal, and can be one of the following three positions (the position can be adjusted with optional parameters).

1. Horizontal text flushed left at the top left of the plot. Terminals that cannot rotate text will probably use this method.

2. Vertical text centered vertically at the left of the plot. Terminals that can rotate text will probably use this method.

3. Horizontal text centered vertically at the left of the plot. The LaTeX and EEPIC drivers use this method. The user must insert line breaks using \\ to prevent the ylabel from overwriting the plot. To produce a vertical row of characters, add \\ between every printing character (but this is ugly).

Syntax:

```
set ylabel {"<label>"} {<xoff>}{,<yoff>}
show ylabel
```

With no parameters, the label is cleared. Specifying constants <xoff> or <yoff> as optional offsets for the label will move the label <xoff> or <yoff> character screen coordinates. For example,

```
set ylabel -1
```

will change only the x offset of the ylabel, moving the label roughly one character width left of its default position. This is especially useful with the LaTeX driver.

(The LaTeX, EEPIC, and Imagen drivers allow \\ in a string to specify a newline.)

18.43 Yrange

The **set yrange** command sets the vertical range that will be displayed. This command turns y axis autoscaling off.

This range may also be specified on the **plot** command line.

Syntax:

```
set yrange [{<ymin> : <ymax>}]
```

where <ymin> and <ymax> terms are constants or expressions.

Both the <ymin> and <ymax> terms are optional. Anything omitted will not be changed, so

```
set yrange [:10]
```

changes ymax to 10 without affecting ymin.

18.44 Ytics

The **set ytics** and **set noytics** commands are similar to the **set xtics** and **set noxtics** commands. Please see **set xtics**.

18.45 Yzeroaxis

set yzeroaxis draws the y-axis. By default, this option is on. **set noyzeroaxis** causes GNUPLOT to omit the y-axis.

Syntax:

```
set yzeroaxis
set noyzeroaxis
show yzeroaxis
```

18.46 Zero

The **zero** value is the default threshold for values approaching 0.0. GNUPLOT will not plot a point if its imaginary part is greater in magnitude than the **zero** threshold. Axis ranges cannot be less than **zero**. The default **zero** value is 1e-8. This can be changed with the **set zero** command.

Syntax:

```
set zero <expression>
show zero
```

18.47 Zeroaxis

set zeroaxis draws the x-axis and y-axis. By default, this option is on. **set nozeroaxis** causes GNUPLOT to omit the axes, and is equivalent to **set noxzeroaxis; set noyzeroaxis.**

Syntax:

```
set zeroaxis
set nozeroaxis
show zeroaxis
```

See **set xzeroaxis** and **set yzeroaxis**.

18.48 Zlabel

The **set zlabel** command sets the z-axis label that is centered along the z axis. Using the optional x,y screen offsets, the label can be placed anywhere on the plot. **set zlabel** with no parameters clears the label.

Syntax:

```
set zlabel {"<label>"} {<xoff>}{,<yoff>}
show zlabel
```

Specifying constants <xoff> or <yoff> as optional offsets for the label will move the label <xoff> or <yoff> character screen coordinates. For example,

```
set zlabel ,1
```

will change only the y offset of the zlabel, moving the label roughly one character height up.

The zlabel will be drawn whenever surfaces or contours are plotted, in the space above the grid level.

(The LaTeX, EEPIC, and Imagen drivers allow \\ in a string to specify a newline.)

18.49 Zrange

The **set zrange** command sets the vertical range that will be displayed. This command turns z axis autoscaling off. The zrange is used only by **splot** and is ignored by **plot**.

This range may also be specified on the **splot** command line.

Syntax:

```
set zrange [{<zmin> : <zmax>}]
```

where <zmin> and <zmax> terms are constants or expressions.

Both the <zmin> and <zmax> terms are optional. Anything omitted will not be changed, so

```
set zrange [2:]
```

changes zmin to 2 without affecting zmax.

18.50 Ztics

The **set ztics** and **set noztics** commands are similar to the **set xtics** and **set noxtics** commands. Please see **set xtics**.

19 Shell

The **shell** command spawns an interactive shell. To return to GNUPLOT, type **logout** if using VMS, **exit** or the END-OF-FILE character if using Unix, **endcli** if using AmigaDOS, or **exit** if using MS-DOS.

A single shell command may be spawned by preceding it with the ! character ($ if using VMS) at the beginning of a command line. Control will return immediately to GNUPLOT after this command is executed. For example, in VMS, AmigaDOS, or MS-DOS,

```
! dir
```

prints a directory listing and then returns to GNUPLOT.

20 Splot

Three-dimensional surface and contour plotting is available in GNUPLOT with the **splot** command. See the **plot** command for features common to the **plot** command.

See also **set contour**, **set cntrparam**, and **set surface**.

21 Start-up

When GNUPLOT is run, it looks for an initialization file to load. This file is called **.gnuplot** on Unix and AmigaDOS systems, and **GNUPLOT.INI** on other systems. If this file is not found in the current directory, the program will look for it in the home directory (under AmigaDOS and MS-DOS, the environment variable GNUPLOT should contain the name of this directory).

If this file is found, GNUPLOT executes the commands in this file. This is most useful for setting the terminal type and defining any functions or variables that are used often.

22 Substitution

Command-line substitution is specified by a system command enclosed in backquotes. This command is spawned and the output it produces replaces the name of the command (and backquotes) on the command line.

Newlines in the output produced by the spawned command are replaced with blanks.

Command-line substitution can be used anywhere on the GNUPLOT command line.

Example:

This will run the program **leastsq** and replace **leastsq** (including backquotes) on the command line with its output:

```
f(x) = `leastsq`
```

or, in VMS

```
f(x) = `run leastsq`
```

23 User-defined

New user-defined variables and functions of one or two variables may be declared and used anywhere.

User-defined function syntax:

```
<function-name> ( <dummy-var1> {,<dummy-var2>} ) =  <expression>
```

where <expression> is defined in terms of <dummy-var1> and <dummy-var2>.

User-defined variable syntax:

```
<variable-name> = <constant-expression>
```

Examples:

```
w = 2
q = floor(tan(pi/2 - 0.1))
f(x) = sin(w*x)
sinc(x) = sin(pi*x)/(pi*x)
delta(t) = (t == 0)
ramp(t) = (t > 0) ? t : 0
min(a,b) = (a < b) ? a : b
comb(n,k) = n!/(k!*(n-k)!)
```

Note that the variable **pi** is already defined.

See **show functions** and **show variables**.

24 Bugs

The bessel functions do not work for complex arguments.

The gamma function does not work for complex arguments.

There is a bug in the stdio library for old Sun operating systems (SunOS Sys4-3.2). The "%g" format for 'printf' sometimes incorrectly prints numbers (e.g., 200000.0 as "2"). Thus, tic mark labels may be incorrect on a Sun4 version of GNUPLOT. A work-around is to rescale the data or use the **set format** command to change the tic mark format to "%7.0f" or some other appropriate format. This appears to have been fixed in SunOS 4.0.

Another bug: On a Sun3 under SunOS 4.0, and on Sun4's under Sys4-3.2 and SunOS 4.0, the 'sscanf' routine incorrectly parses "00 12" with the format "%f %f" and reads 0 and 0 instead of 0 and 12. This affects data input. If the data file contains x coordinates that are zero but are specified like '00', '000',

etc, then you will read the wrong y values. Check any data files or upgrade the SunOS. It appears to have been fixed in SunOS 4.1.1.

Microsoft C 5.1 has a nasty bug associated with the %g format for printf. When any of the formats "%.2g", "%.1g", "%.0g", "%.g" are used, printf will incorrectly print numbers in the range 1e-4 to 1e-1. Numbers that should be printed in the %e format are incorrectly printed in the %f format, with the wrong number of zeros after the decimal point.

To work around this problem, use the %e or %f formats explicitly.

GNUPLOT, when compiled with Microsoft C, did not work correctly on two VGA displays that were tested. The CGA, EGA and VGA drivers should probably be rewritten to use the Microsoft C graphics library. GNUPLOT compiled with Turbo C uses the Turbo C graphics drivers and does work correctly with VGA displays.

VAX/VMS 4.7 C compiler release 2.4 also has a poorly implemented %g format for printf. The numbers are printed numerically correct, but may not be in the requested format. The K&R second edition says that for the %g format, %e is used if the exponent is less than -4 or greater than or equal to the precision. The VAX uses %e format if the exponent is less than -1. The VAX appears to take no notice of the precision when deciding whether to use %e or %f for numbers less than 1. To work around this problem, use the %e or %f formats explicitly. From the VAX C 2.4 release notes: e,E,f,F,g,G Result will always contain a decimal point. For g and G, trailing zeros will not be removed from the result.

VAX/VMS 5.2 C compiler release 3.0 has a slightly better implemented %g format than release 2.4, but not much. Trailing decimal points are now removed, but trailing zeros are still not removed from %g numbers in exponential format.

ULTRIX X11R3 has a bug that causes the X11 driver to display "every other" plot. The bug seems to be fixed in DEC's release of X11R4 so newer releases of ULTRIX don't seem to have the problem. Solutions for older sites include upgrading the X11 libraries (from DEC or direct from MIT) or defining ULTRIX_KLUDGE when compiling the x11.trm file. Note that the kludge is not an ideal fix, however.

The constant HUGE was incorrectly defined in the NeXT OS 2.0 operating system. HUGE should be set to 1e38 in plot.h. This error has been corrected in the 2.1 version of NeXT OS.

Some older models of HP plotters do not have a page eject command 'PG'. The current HPGL driver uses this command in HPGL_reset. This may need to be removed for these plotters. The current PCL5 driver uses HPGL/2 for text as well as graphics. This should be modified to use scalable PCL fonts.

Please report any bugs to bug-gnuplot@ames.arc.nasa.gov.